


Fastener SuperStore Finished Hex Nuts



Thread Diameter	Coarse TPI	Fine TPI	Width Across Flats F	Width Across Corners G	Thickness H
1/4	-20	-28	7/16	0.488 - 0.505	7/32
5/16	-18	-24	1/2	0.557 - 0.577	17/64
3/8	-16	-24	9/16	0.628 - 0.650	21/64
7/16	-14	-20	11/16	0.768 - 0.794	3/8
1/2	-13	-20	3/4	0.840 - 0.866	7/16
9/16	-12	-18	7/8	0.982 - 1.010	31/64
5/8	-11	-18	15/16	1.051 - 1.083	35/64
3/4	-10	-16	1 1/8	1.240 - 1.299	41/64
7/8	-9	-14	1 5/16	1.447 - 1.516	3/4
1	-8	-14	1 1/2	1.653 - 1.732	55/64
1 1/8	-7	-12	1 11/16	1.859 - 1.949	31/32
1 1/4	-7	-12	1 7/8	2.066 - 2.165	1 1/16
1 3/8	-6	-12	2 1/16	2.273 - 2.382	1 11/64
1 1/2	-6	-12	2 1/4	2.480 - 2.598	1 9/32
1 5/8	-6	-12	2 7/16	2.686 - 2.815	1 25/64
1 3/4	-5	-12	2 5/8	2.893 - 3.030	1 1/2
2	-4.5	-12	3	3.305 - 3.464	1 23/32
2 1/4	-4.5	-12	3 3/8	3.718 - 3.897	1 15/16
2 1/2	-4	-12	3 3/4	4.133 - 4.331	2 5/32
2 3/4	-4	--	4 1/8	4.456 - 4.763	2 3/8
3	-4	--	4 1/2	4.959 - 5.195	2 19/32

Materials: Low Carbon Steel -- available in Zinc, Hot Dip Galvanized & Black Oxide Finishes
 Grade 5 -- AISI 1008 - 1026 or Equiv Steel. Rockwell C32 Max. Core Hardness
 Grade 8 -- AISI 1021 - 1045 or Equiv Steel.
 18-8 Stainless Steel & 316 Stainless Steel