

1N5283 THRU 1N5314

**SILICON CURRENT LIMITING DIODES**



www.centrasemi.com

**DESCRIPTION:**

The CENTRAL SEMICONDUCTOR 1N5283 series types are silicon field effect current regulator diodes designed for applications requiring a constant current over a wide voltage range. These devices are manufactured in the cost effective DO-35 double plug case which provides many benefits to the user, including space savings and improved thermal characteristics. Special selections of  $I_p$  (regulator current) are available for critical applications.



**DO-35 CASE**

**FEATURES:**

- High Reliability
- Superior Lot To Lot Consistency
- Special Selections Available
- Surface Mount Devices Available

**MAXIMUM RATINGS:** ( $T_L=75^\circ\text{C}$ )

Peak Operating Voltage  
Power Dissipation  
Operating and Storage Junction Temperature

**SYMBOL**

$P_{OV}$  100  
 $P_D$  600  
 $T_J, T_{stg}$  -65 to +200

**UNITS**

V  
mW  
 $^\circ\text{C}$

**ELECTRICAL CHARACTERISTICS:** ( $T_A=25^\circ\text{C}$ )

Type	Regulator Current (Note 1) $I_p @ V_T=25\text{V}$			Minimum Dynamic Impedance $Z_T @ V_T=25\text{V}$	Minimum Knee Impedance $Z_K @ V_K=6.0\text{V}$	Maximum Limiting Voltage $V_L @ I_L=0.8 \times I_p \text{ MIN}$
	MIN mA	NOM mA	MAX mA	MΩ	MΩ	V
1N5283	0.187	0.22	0.253	25	2.75	1.0
1N5284	0.204	0.24	0.276	19	2.35	1.0
1N5285	0.230	0.27	0.311	14	1.95	1.0
1N5286	0.255	0.30	0.345	9.0	1.60	1.0
1N5287	0.281	0.33	0.380	6.6	1.35	1.0
1N5288	0.332	0.39	0.449	4.1	1.00	1.05
1N5289	0.366	0.43	0.495	3.3	0.87	1.05
1N5290	0.400	0.47	0.541	2.7	0.75	1.05
1N5291	0.476	0.56	0.644	1.90	0.56	1.10
1N5292	0.527	0.62	0.713	1.55	0.47	1.13
1N5293	0.578	0.68	0.782	1.35	0.40	1.15
1N5294	0.638	0.75	0.863	1.15	0.335	1.20
1N5295	0.697	0.82	0.943	1.00	0.29	1.25
1N5296	0.774	0.91	1.05	0.88	0.24	1.29
1N5297	0.850	1.00	1.15	0.80	0.205	1.35
1N5298	0.935	1.10	1.27	0.70	0.18	1.40

Notes: (1) Pulsed Method: Pulse Width (ms) = 27.5 divided by  $I_p$  NOM (mA)

R4 (7-February 2013)

**1N5283 THRU 1N5314**  
**SILICON CURRENT LIMITING DIODES**



**ELECTRICAL CHARACTERISTICS - Continued:** ( $T_A=25^\circ\text{C}$ )

Type	Regulator Current (Note 1) $I_P @ V_T=25V$			Minimum Dynamic Impedance $Z_T @ V_T=25V$	Minimum Knee Impedance $Z_K @ V_K=6.0V$	Maximum Limiting Voltage $V_L @ I_L=0.8 \times I_P \text{ MIN}$
	MIN mA	NOM mA	MAX mA	$M\Omega$	$M\Omega$	V
1N5299	1.02	1.20	1.38	0.640	0.155	1.45
1N5300	1.11	1.30	1.50	0.580	0.135	1.50
1N5301	1.19	1.40	1.61	0.540	0.115	1.55
1N5302	1.28	1.50	1.73	0.510	0.105	1.60
1N5303	1.36	1.60	1.84	0.475	0.092	1.65
1N5304	1.53	1.80	2.07	0.420	0.074	1.75
1N5305	1.70	2.00	2.30	0.395	0.061	1.85
1N5306	1.87	2.20	2.53	0.370	0.052	1.95
1N5307	2.04	2.40	2.76	0.345	0.044	2.00
1N5308	2.30	2.70	3.11	0.320	0.035	2.15
1N5309	2.55	3.00	3.45	0.300	0.029	2.25
1N5310	2.81	3.30	3.80	0.280	0.024	2.35
1N5311	3.06	3.60	4.14	0.265	0.020	2.50
1N5312	3.32	3.90	4.49	0.255	0.017	2.60
1N5313	3.66	4.30	4.95	0.245	0.014	2.75
1N5314	4.00	4.70	5.41	0.235	0.012	2.90

**DO-35 CASE - MECHANICAL OUTLINE**



<b>DIMENSIONS</b>				
SYMBOL	INCHES		MILLIMETERS	
	MIN	MAX	MIN	MAX
A	0.018	0.022	0.46	0.56
B	0.120	0.200	3.05	5.08
C	0.060	0.090	1.52	2.29
D	1.000	-	25.40	-

DO-35 (REV: R1)

R1

R4 (7-February 2013)

# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

## Central Semiconductor:

[1N5285](#) [1N5289](#) [1N5292](#) [1N5293](#) [1N5297](#) [1N5306](#) [1N5308](#) [1N5310](#) [1N5311](#) [1N5300](#) [1N5284](#) [1N5286](#)  
[1N5287](#) [1N5288](#) [1N5290](#) [1N5291](#) [1N5294](#) [1N5295](#) [1N5296](#) [1N5298](#) [1N5299](#) [1N5301](#) [1N5302](#) [1N5303](#) [1N5304](#)  
[1N5309](#) [1N5312](#) [1N5307\\_PB](#) [1N5314](#) [1N5294 TR](#) [1N5284 TR](#) [1N5304 TR](#) [1N5301 TR](#) [1N5290 TR](#) [1N5283 TR](#)  
[1N5293 TR](#) [1N5300 TR](#) [1N5307 TR](#) [1N5287 TR](#) [1N5310 TR](#) [1N5306 TR](#) [1N5285 TR](#) [1N5298 TR](#) [1N5286 TR](#)  
[1N5296 TR](#) [1N5288 TR](#) [1N5312 TR](#) [1N5291 TR](#) [1N5313 TR](#) [1N5297 TR](#) [1N5289 TR](#) [1N5308 TR](#) [1N5295 TR](#)  
[1N5314 TR](#) [1N5311 TR](#) [1N5303 TR](#) [1N5309 TR](#) [1N5299 TR](#) [1N5305 TR](#) [1N5292 TR](#) [1N5302 TR](#) [1N5299 BK](#)  
[1N5307 BK](#)