



features

- Marking: 1F, 1H: no marking, black body
1E: blue body, no marking
1J: three-digit black marking (E-24 only)
on blue protective coat. 2A ~ 3A four-digit
black marking on blue protective coat.
- Products with lead-free terminations meet EU RoHS requirements. EU RoHS regulation is not intended for Pb-glass contained in electrode, resistor element and glass.
- AEC-Q200 Qualified: 0201 (1H), 0402 (1E), 0603 (1J), 0805 (2A), 1206 (2B), 1210 (2E), 2010 (2H/W2H), 2512 (3A/W3A/W3A2)


dimensions and construction



Derating Curve



For resistors operated at an ambient temperature of 70°C or above, a power rating shall be derated in accordance with the above derating curve.



For resistors operated at a terminal part temperature of described for each size or above, a power rating shall be derated in accordance with the above derating curve. Please refer to "Introduction of the derating curve based on the terminal part temperature" in the beginning of our catalog before use.

Type* (Inch Size Code)	Dimensions inches (mm)				
	L	W	c	d	t
1F (01005)	.016±.0008 (0.4±0.02)	.008±.0008 (0.2±0.02)	.004±.001 (0.1±0.03)	.004±.001 (0.11±0.03)	.005±.0008 (0.13±0.02)
1H (0201)	.024±.001 (0.6±0.03)	.012±.001 (0.3±0.03)	.004±.002 (0.1±0.05)	.006±.002 (0.15±0.05)	.009±.001 (0.23±0.03)
1E (0402)	.039 +.004 -.002 (1.0 +0.1 -.05)	.02±.002 (0.5±0.05)	.008±.004 (0.2±0.1)	.01 +.002 -.004 (0.25 +0.05 -.01)	.014±.002 (0.35±0.05)
1J (0603)	.063±.008 (1.6±0.2)	.031±.004 (0.8±0.1)	.012±.004 (0.3±0.1)	.012±.004 (0.3±0.1)	.018±.004 (0.45±0.1)
2A (0805)	.079±.008 (2.0±0.2)	.049±.004 (1.25±0.1)	.016±.008 (0.4±0.2)	.012 +.008 -.004 (0.3 +0.2 -.01)	.02±.004 (0.5±0.1)
2B (1206)	.126±.008 (3.2±0.2)	.063±.008 (1.6±0.2)	.02±.012 (0.5±0.3)	.016 +.008 -.004 (0.4 +0.2 -.01)	.024±.004 (0.6±0.1)
2E (1210)		.102±.008 (2.6±0.2)			
2H (2010)	.197±.008 (5.0±0.2)	.098±.008 (2.5±0.2)			
W2H (2010)					
3A (2512)	.248±.008 (6.3±0.2)	.122±.008 (3.1±0.2)		.016 +.008 -.004 (0.4 +0.2 -.01)	
W3A/W3A2 (2512)				.026±.006 (0.65±0.15)	

* Parentheses indicate EIA package size codes.

ordering information

New Part #	RK73H	2B	T	TD	1003	F
Type		Size	Termination Material	Packaging	Nominal Resistance	Tolerance
		1F 1H 1E 1J 2A 2B 2E 2H W2H W3A 2H 3A New W3A2	T: Sn (1F ~ W3A2) Contact factory for below options: L: SnPb (1E, 1J, 2A, 2B, 2E, 2H, 3A) G: Au (1E ~ 2A: 10Ω ~ 1MΩ)	TX: 01005 only: 4mm width - 1mm pitch plastic embossed TBL: 01005 only: 2mm pitch pressed paper TA: 0201 only: 1mm pitch pressed paper TC: 0201 only: 7" 2mm pitch pressed paper (TC: 10,000 pcs/reel, TCM: 15,000 pcs/reel) TCD: 0201 only: 10" 2mm pitch pressed paper TPD: 0402 only: 10" plastic embossed TPL: 0402 only: 2mm pitch punch paper TP: 0402, 0603, 0805: 7" 2mm pitch punch paper TD: 0603, 0805, 1206, 1210: 7" 4mm pitch punched paper TDD: 0603, 0805, 1206, 1210: 10" paper tape TE: 0805, 1206, 1210, 2010 & 2512: 7" embossed plastic TED: 0805, 1206, 1210, 2010 & 2512: 10" embossed plastic For further information on packaging, please refer to Appendix A	3 significant figures + 1 multiplier "R" indicates decimal on value <100Ω	D: ±0.5% F: ±1%



KOA SPEER ELECTRONICS, INC.

applications and ratings

RK73H

precision 0.5%, 1% tolerance
thick film chip resistor

	Part Designation	Power Rating	Rated Ambient Temp.	Rated Terminal Part Temp.	T.C.R. (x10 ⁻⁶ /K)	Resistance Range		Maximum Working Voltage	Maximum Overload Voltage	Operating Temperature Range					
						D±0.5% E-24, E-96	F±1% E-24, E-96								
NEW	RK73H1F (01005)	0.03W	70°C	—	±200	—	100kΩ - 1MΩ ¹	20V	30V	-55°C to +125°C					
	RK73H1H (0201)	0.05W			±250	—	10Ω - 91kΩ ¹	25V	50V	-55°C to +155°C					
					±200	10Ω - 1MΩ	10Ω - 10MΩ ¹								
					±400	—	1.0Ω - 9.1Ω ¹								
	RK73H1E (0402)	0.1W		125°C	±100	10Ω - 1MΩ	10Ω - 1MΩ	50V	100V						
					±200	—	1.0Ω - 9.76Ω 1.02MΩ - 10MΩ	75V							
					RK73H1J (0603)	0.1W	±100				1.02kΩ - 1MΩ	1.02kΩ - 1MΩ	150V	200V	
							±200				—	1.02MΩ - 10MΩ			
							0.125W				±100	10Ω - 1kΩ			10Ω - 1kΩ
											±200	—			1.0Ω - 9.76Ω
	RK73H2A (0805)	0.25W			±100	10Ω - 1MΩ	10Ω - 1MΩ	200V	400V						
					±200	—	1.0Ω - 9.76Ω								
					±400	—	1.02MΩ - 10MΩ								
	RK73H2B (1206)	0.25W			±100	10Ω - 1MΩ	10Ω - 1MΩ	200V	400V						
					±200	—	1.0Ω - 9.76Ω 1.02MΩ - 5.6MΩ								
					±400	—	5.62MΩ - 10MΩ								
	RK73H2E (1210)	0.5W		±100	10Ω - 1MΩ	10Ω - 1MΩ	200V*			400V*					
				±200	—	1.0Ω - 9.76Ω 1.02MΩ - 5.6MΩ									
				±400	—	5.62MΩ - 10MΩ									
	RK73HW2H/2H (2010)	0.75W		±100	10Ω - 1MΩ	10Ω - 1MΩ	200V			400V					
				±200	—	1.0Ω - 9.76Ω 1.02MΩ - 5.6MΩ									
				±400	—	5.62MΩ - 10MΩ									
	RK73HW3A/3A (2512)	1.0W		±100	10Ω - 1MΩ	10Ω - 1MΩ	200V	400V							
				±200	—	1.0Ω - 9.76Ω 1.02MΩ - 5.6MΩ									
				±400	—	5.62MΩ - 10MΩ									
	RK73HW3A2 (2512)	2.0W		—	95°C	±100	10Ω - 1MΩ	10Ω - 1MΩ	200V	400V					
						±200	—	1.0Ω - 9.76Ω 1.02MΩ - 5.6MΩ							
						±400	—	5.62MΩ - 10MΩ							

Rated voltage = $\sqrt{\text{Power rating} \times \text{resistance value}}$ or max. working voltage, whichever is lower
¹ 1F: 10-1MΩ; E-24, 1H: 1.0-9.1, 1M-10MΩ; E-24. If any questions arise whether to use the "Rated Ambient Temperature" or the "Rated Terminal Part Temperature," please give priority to the "Rated Terminal Part Temperature." Prior to use and for more details refer to "Introduction of the derating curves based on the terminal part temperature" in the beginning of the catalog.
 *Contact KOA prior to usage for Max. Working Voltage and Max. Overload Voltage. While using under high power, the temperature of the product may increase depending on the condition of heat dissipation from PCB. Be sure to check the terminal part temperature as well as precautions to use on delivery specification before use.

environmental applications

Performance Characteristics

Parameter	Requirement Δ R (%+0.1Ω)		Test Method
	Limit	Typical	
Resistance	Within specified tolerance	—	25°C
T.C.R.	Within specified T.C.R.	—	+25°C/-55°C and +25°C/+125°C
Overload (Short time)	±2%	±1%: 1F ±0.5%: Another	Rated Voltage x 2.5 for 5 seconds (1E, 2B, W3A2: Rated Voltage x 2 for 5 seconds)
Resistance to Soldering Heat	±1%: 1F ~ W3A2 (10Ω ≤ R ≤ 1MΩ); ±3%: 1H ~ W3A2 (R < 10Ω, R > 1MΩ)	±0.5%: 1F ~ W3A2 (10Ω < R < 1MΩ); ±1%: 1H ~ W3A2 (R < 10Ω, R > 1MΩ)	260°C ± 5°C, 10 seconds ± 1 second
Rapid Change of Temperature	±1%: 1F ±0.5%: Another	±0.5%: 1F ±0.3%: Another	-55°C (30 minutes), +125°C (30 minutes), 100 cycles
Moisture Resistance	±2%: 1J, 2A, 2B ±3%: Another	±0.75%: 1J, 2A, 2B; ±1.5%: 1F, ±1%: Another	40°C ± 2°C, 90%-95% RH, 1000 hours, 1.5 hr ON, 0.5 hr OFF cycle
Endurance at 70°C	±2%: 1J, 2A, 2B ±3%: Another	±0.75%: 1J, 2A, 2B ±1%: Another	70°C ± 2°C, 1000 hours, 1.5 hr ON, 0.5 hr OFF cycle
High Temperature Exposure	±1%	±0.5%: 1F ±0.3%: Another	+125°C, 1000 hours: 1F; +155°C, 1000 hours: 1E, 1H, 1J, 2A, 2B, 2E, 2H/W2H, 3A/W3A/W3A2

Specifications given herein may be changed at any time without prior notice. Please confirm technical specifications before you order and/or use.

11/15/16

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

KOA Speer:

[RK73H2ELTE33R2F](#) [RK73H2ELTE3321F](#) [RK73H1ELTP5104F](#) [RK73H1ELTP6982F](#) [RK73H2HLTE3R32F](#)
[RK73H1JLTD1021F](#) [RK73H2BLTD2872F](#) [RK73H2BLTD2264F](#) [RK73H1JLTD28R7F](#) [RK73H1ELTP6980F](#)
[RK73H1ELTP3653F](#) [RK73H2BLTD2260F](#) [RK73H1JLTD10R2F](#) [RK73H2BLTD1651F](#) [RK73H2ELTD4753F](#)
[RK73H2ALTE3241F](#) [RK73H2BLTD2873F](#) [RK73H2BLTD2263F](#) [RK73H1ETTP6982F](#) [RK73H1ELTP5101F](#)
[RK73H2ELTE3323F](#) [RK73H2BLTE6342F](#) [RK73H1ELTP3651F](#) [RK73H1ELTP5103F](#) [RK73H2ALTD1691F](#)
[RK73H2BLTD24R3F](#) [RK73H1ELTP68R1F](#) [RK73H2ALTD5361F](#) [RK73H2ALTD5363F](#) [RK73H2ELTD3011F](#)
[RK73H2BTDD6R04F](#) [RK73H1JLTD17R8F](#) [RK73H1JLTD2803F](#) [RK73H1ELTP2102F](#) [RK73H2ATTDD4324F](#)
[RK73H1ELTP2101F](#) [RK73H2BLTD6190F](#) [RK73H2BLTDD2003F](#) [RK73H2ELTE2610F](#) [RK73H1ELTP2103F](#)
[RK73H2BLTD6192F](#) [RK73H2ALTD54R9F](#) [RK73H2ATTDD1402D](#) [RK73H1JLTD71R5F](#) [RK73H1JLTD2802F](#)
[RK73H2BLTD6194F](#) [RK73H2BLTD2R74F](#) [RK73H2ALTD2201F](#) [RK73H2ELTD3010F](#) [RK73H1JLTD2800F](#)
[RK73H2BLTD6193F](#) [RK73H2ELTD3013F](#) [RK73H2BLTD6191F](#) [RK73H1ELTP2100F](#) [RK73H2ELTD3012F](#)
[RK73H1JLTD2801F](#) [RK73H1JLTD3320F](#) [RK73H2BLTE4022F](#) [RK73H2ALTD5492F](#) [RK73H2ALTD2R43F](#)
[RK73H3ALTE9090F](#) [RK73H1JLTD5622F](#) [RK73H2ALTE5622F](#) [RK73H1JLTD2872F](#) [RK73H2ALTD60R4F](#)
[RK73H2BLTD2R87F](#) [RK73H1JLTD3321F](#) [RK73H2ALTD16R5F](#) [RK73H2BLTD1503F](#) [RK73H1JLTD2871F](#)
[RK73H2BLTE4020F](#) [RK73H2ELTD1623F](#) [RK73H1JLTD2873F](#) [RK73H1JLTD33R2F](#) [RK73H2ALTD16R0F](#)
[RK73H2ALTD5493F](#) [RK73H2ELTD16R2F](#) [RK73H1JLTD3324F](#) [RK73H1JLTD5623F](#) [RK73H2BTDD8R66F](#)
[RK73H2ALTE5620F](#) [RK73H2ALTD1622F](#) [RK73H2ELTD1621F](#) [RK73H2ALTD2R49F](#) [RK73H2ALTE27R4F](#)
[RK73H1JLTD5620F](#) [RK73H1JLTD3322F](#) [RK73H2ELTD60R4F](#) [RK73H2ALTD1623F](#) [RK73H2ALTD1620F](#)
[RK73H1JLTD3322D](#) [RK73H2ALTD1624F](#) [RK73H2ALTD5490F](#) [RK73H2BLTD1501F](#) [RK73H1JLTD56R0F](#)
[RK73H2ALTD16R9F](#) [RK73H1ELTP5232F](#) [RK73H1ELTP10R7F](#) [RK73H2ATTDD2152F](#) [RK73H2BLTE1820F](#)